

ABC SHOT PEENER



TECHNICAL SPECIFICATIONS (Direct Pressure)

CABINET CONSTRUCTION 14 GAUGE REINFORCED CONTINUOUSLY WELDED	<table border="1"> <thead> <tr> <th data-bbox="784 1218 1105 1312">Air (approximate requirements) CFM</th> <th data-bbox="1114 1218 1273 1312">40 PSI</th> <th data-bbox="1281 1218 1440 1312">60 PSI</th> <th data-bbox="1448 1218 1578 1312">80 PSI</th> </tr> </thead> <tbody> <tr> <td data-bbox="784 1314 1105 1360">3/16" Nozzle</td> <td data-bbox="1114 1314 1273 1360">21</td> <td data-bbox="1281 1314 1440 1360">32</td> <td data-bbox="1448 1314 1578 1360">41</td> </tr> <tr> <td data-bbox="784 1362 1105 1423">1/4" Nozzle</td> <td data-bbox="1114 1362 1273 1423">41</td> <td data-bbox="1281 1362 1440 1423">56</td> <td data-bbox="1448 1362 1578 1423">72</td> </tr> <tr> <td data-bbox="784 1425 1105 1486">5/16" Nozzle</td> <td data-bbox="1114 1425 1273 1486">64</td> <td data-bbox="1281 1425 1440 1486">88</td> <td data-bbox="1448 1425 1578 1486">113</td> </tr> </tbody> </table>				Air (approximate requirements) CFM	40 PSI	60 PSI	80 PSI	3/16" Nozzle	21	32	41	1/4" Nozzle	41	56	72	5/16" Nozzle	64	88	113
Air (approximate requirements) CFM	40 PSI	60 PSI	80 PSI																	
3/16" Nozzle	21	32	41																	
1/4" Nozzle	41	56	72																	
5/16" Nozzle	64	88	113																	
FINISH DURABLE ENAMEL PRIMED AND PAINTED. CORROSION RESISTANT																				
WORKING CHAMBER DIMENSIONS: 36" W X 36" D X 30" H SAFETY DOOR INTERLOCKS SELF ADJUSTING DOOR LATCHES FULL LENGTH HINGES																				
VIEWING WINDOW 12 1/2" H X 21" W QUICK CHANGE, SQUARE CORNERED TEMPERED GLASS																				
DUST COLLECTOR SPECIFICATIONS																				
D10 Pull Through		RPJ2H / DC Hopper																		
(700 CFM) 42" W X 25" D X 80" H 1 HP Motor - 25 Dust Bags		5' 10" x 2' 6" x 12' 2 - 36" Cartridges Automatic Reverse																		

LIGHTING

TWO TUBE, 24" FLUORESCENT FIXTURE
LOW TEMPERATURE
SHIELDED, EXTERNALLY LOCATED
120 V, 60 HZ

GLOVES

ABRASIVE RESISTANT, CLOTH LINED
8" PADDED ARM HOLE PORTS
STATIC RESISTANT GAUNTLET

HOSES

1/2" ID LIGHTWEIGHT, FLEXIBLE
ABRASIVE RESISTANT

BLOW - OFF GUN

FINGERTIP CONTROL BLOW - OFF NOZZLE

PRESSURE POT

ASME CODED, ONE CU. FT. CAPACITY
AIR PRESSURE, REMOTE CONTROLLED
AUTOMATIC REFILLING POT
HEAVY DUTY SCREEN DRAWER
3/4" PIPING
ADJUSTABLE MEDIA VALVE
AUTOMATIC BLOW DOWN
MOISTURE SEPARATOR

BLAST NOZZLE

TUNGSTEN CARBIDE, 1/4" STANDARD

Manual Pneumatic Bag Shaker	Pulse Cleaning
RPJ2 / DC Drawer	Dust Bag
5' 10" x 2' 6" x 7' 9" 2 - 36" Cartridges Automatic Reverse Pulse Cleaning	1 Bag with 400 CFM Blower Zipper Bottom 100% Cotton Sateen

OTHER
3636P - 4836P - 6036-P
MODELS

ABC 4836P





Model Number	Description	Floor Area (W)	Required (D)
	ABC 3636P		
ABC 3636P	Cabinet Only, less Blower & DC *	108"	67"
ABC 3636P - 400DB	400 CFM Blower with Dust Bag	108"	88"
ABC 3636P - D10	700 CFM Blower with D-10 DC	108"	108"
ABC 3636P - M2DC	700 CFM Blower with M2 DC	108"	108"
	ABC 4836P		
ABC 4836P	Cabinet Only, less Blower & DC *	112"	67"
ABC 4836P - 400DB	400 CFM Blower with Dust Bag	112"	88"
ABC 4836P - D10	700 CFM Blower with D-10 DC	112"	108"
ABC 4836P - M2DC	700 CFM Blower with M2 DC	112"	108"
	ABC 6036P		
ABC 6036P	Cabinet Only, less Blower & DC *	120"	67"
ABC 6036P - 400DB	400 CFM Blower with Dust Bag	120"	88"
ABC 6036P - D10	700 CFM Blower with D-10 DC	120"	108"
ABC 6036P - M2DC	700 CFM Blower with M2 DC	120"	108"

* For Connection to in - Plant Dust Collector - ** Not pictured