

BLAST-IT-ALL®

MODEL 247



LARRY HESS & ASSOCIATES, INC.

P.O. BOX 1615

SALISBURY, NC 28145-1615

PHONE: 1-800-535-2612

FAX: 704-638-9311

www.blast-it-all.com

sales@blast-it-all.com

4836 -- SYSTEM PARTICULARS

- Cyclone separator sized for cabinet size and media type
- Fluorescent lighting with tempered glass protectors
- Snap-In (QUICK CHANGE) cloth lined gloves
- Padded arm rests for operator comfort
- Safety tempered glass viewing window
- Mylar dispenser with Roll Mylar to protect window (Roll 10 ft long)
- Cabinet air inlet silencers
- All pneumatic blast and safety controls
- Floating foot blast control
- Magnehelic gauge for dust filter monitoring
- Manual operator cartridge pulse cleaning
- Adjustable door latches
- Media load station on sump at load door
- Vibrator on debris screen with regulator and control
- Overall dimensions 52" wide x 72" deep x 82" high
- Working cabinet inside dimensions 48" wide x 36" deep x 42" high
- Door opening see insert
- Carbide nozzle standard
- Filtration area 103 sq. ft per cartridge (2) cartridge for 700 CFM
- Dust Blow-off nozzle
- Exhaust fan 700 system, 1 hp single phase
- Electrical Single point connection
- One cu ft pressure pot with Micro Valve and Quick blow down controls
- Shipping weight 700 pressure system 1500 LB

6048 -- SYSTEM PARTICULARS

- Cyclone separator sized for cabinet size and media type
- Fluorescent lighting with tempered glass protectors
- Snap-In (QUICK CHANGE) cloth lined gloves
- Padded arm rests for operator comfort
- Safety tempered glass viewing window
- Mylar dispenser with Roll Mylar to protect window (Roll 10 ft long)
- Cabinet air inlet silencers
- All pneumatic blast and safety controls
- Floating foot blast control
- Magnehelic gauge for dust filter monitoring
- Manual operator cartridge pulse cleaning
- Adjustable door latches
- Media load station on sump at load door
- Vibrator on debris screen with regulator and control
- Overall dimensions 62" wide x 84" deep x 82" high
- Working cabinet inside dimensions 60" wide x 48" deep x 42" high
- Door opening see insert
- Carbide nozzle standard
- Filtration area 103 sq. ft per cartridge (3) cartridge for 900 CFM
- Dust Blow-off nozzle
- Exhaust fan 900 CFM system, 2 hp three phase
- Electrical Single point connection
- Three phase electrical has step-down transformer for 120 V controls
- One cu ft pressure pot with Micro Valve and Quick blow down controls
- Shipping weight 900 CFM pressure system 1800 LB

AVAILABLE STANDARD OPTIONS

- b Cabinet and Reclaim wear package
- b Heavy duty flex duct
- b Manual set-in turntable
- b Turntable and track assemblies
- b Automatic pulse controls for collector